




see what Delta can do™

## Pendant Raincan

- H<sub>2</sub>Okinetic® Pendant Raincan
- Single Spray Setting Pendant Raincan
- LED light on each spray face




57140▲-25-L


57190▲-25-L

Submitted Model No.:

Specific Features:



57140▲-25-L



57190▲-25-L

▲ Designate proper finish suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or [www.deltafaucet.com](http://www.deltafaucet.com) for finish options and product availability.

DSP-B-57140-25-L Rev. A

### STANDARD SPECIFICATIONS:

- Maximum 2.5 gpm @ 80 psi, 9.5 L/min @ 550 kPa
- Adjustable pendant shower heads for ideal coverage
- To be used with a 9' (2286 mm) ceiling or taller
- Connects to 1/2" IPS male threads
- LED lights are powered by hydrogenerator. No batteries required.

### WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

### COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1

### Delta Faucet Company

55 E. 111th Street, Indianapolis, Indiana 46280  
 350 South Edgeware Road, St. Thomas, Ontario Canada N5P 4L1  
 © 2018 Delta Faucet Company