Clayton® 60" x 32" Soaker Bathtub Tile-in

FEATURES

- 60" x 32" x 24-1/2"
- 3-sided molded integral flange tub standard
- Luxuriously deep bathing well
- Cast-acrylic construction provides high durability
- Slip-resistant surface
- Optional solid brass grab bar with various finishes
- Molded integral flange options available through special order: 0 flange, 1 flange, 2 flange.

MODELS

- ABY782P
 Acrylic bathtub. Slip-resistant surface.
 Left drain/3 flange
- ABY782Q
 Acrylic bathtub. Slip-resistant surface.

 Right drain/3 flange

COLORS/FINISHES

- Shell Color #01 Cotton #12 Sedona Beige
- Grab Bar
 #CP Polished Chrome
 #BN Brushed Nickel
 #PN Polished Nickel

CODES/STANDARDS

- Meets and exceeds ANSI Z124.1.2, CSA B45
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others



PRODUCT SPECIFICATION

The TOTO® Clayton® Soaker Bathtub Tile-in shall have a 3-sided molded integral flange tub standard and a luxuriously deep bathing well. The Soaker Bathtub shall have a cast-acrylic construction that provides high durability with a slip-resistant surface. The Soaker Bathtub shall have an optional solid brass grab bar with various finishes. Soaker Bathtub shall be TOTO Model ABY782_____.



Clayton® 60" x 32" Soaker Bathtub Tile-in

SPECIFICATIONS

Size 60"L x 32"W
 Depth 20-1/4"
 Water Depth 14.1"

Warranty
 1 Year Limited Warranty on

acrylic tub

1 Year Limited Warranty on components and parts


Material Lucite Cast Acrylic


Shipping Weight 76 lbs.


Shipping Dimensions 68"L x 39"W x 27"H
 Gallons 74 to overflow

INSTALLATION NOTES

Floor support under bath must provide a minimum of 75 lbs/square foot (366 kg/square meter) loading.







TOTO_®